FCC 47 CFR PART 15 SUBPART B & IC ICES-003 TEST REPORT

for

Digital Satellite Receiver

MODEL: DBS6600 MINI

Data Applies To: DBS8000

Brand : LEXIUM

Test Report Number:
111025404-D

Issued for

WS International
1200 Cobb Parkway North Suite 100B Marietta, Georgia 30062 USA

Issued By:

Compliance Certification Services Inc.
Tainan BU.
No.8,Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)

TEL: 886-6-5802201
FAX: 886-6-5802202

Issued Date: November 8, 2011

Note: *This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.*

Revision History

Rev.		Issue Date		Revisions	Effect Page	Revised By
00		November 8, 2011		Initial Issue	ALL	Eva Lin

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION 4
2 EUT DESCRIPTION 5
3 TEST METHODOLOGY 6
3.1. DECISION OF FINAL TEST MODE 6
3.2. EUT SYSTEM OPERATION 6
3.3. DESCRIPTION OF SUPPORT UNITS 7
3.4. CONFIGURATION OF SYSTEM UNDER TEST 7
4 FACILITIES AND ACCREDITATIONS 8
4.1. FACILITIES 8
4.2. ACCREDITATIONS 8
4.3. MEASUREMENT UNCERTAINTY 9
5 CONDUCTED EMISSION MEASUREMENT 10
5.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT 10
5.2. TEST INSTRUMENTS 10
5.3. TEST PROCEDURES 11
5.4. TEST SETUP 12
5.5. DATA SAMPLE: 12
5.6. TEST RESULTS 13
6 RADIATED EMISSION MEASUREMENT 15
6.1. LIMITS OF RADIATED EMISSION MEASUREMENT 15
6.2. TEST INSTRUMENTS 17
6.3. TEST PROCEDURES 18
6.4. TEST SETUP 19
6.5. DATA SAMPLE 20
6.6. TEST RESULTS 21
7 ANTENNA POWER MEASUREMENT (SECTION 15.111) 24
7.1. LIMITS OF ANTENNA POWER CONDUCTED MEASUREMENT 24
7.2. TEST INSTRUMENTS 24
7.3. TEST PROCEDURES 25
7.4. DATA SAMPLE: 26
7.5. TEST RESULTS 27
8 PHOTOGRAPHS OF THE TEST CONFIGURATION 28
APPENDIX 1 - PHOTOGRAPHS OF EUT A1

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1 TEST RESULT CERTIFICATION

Product:	Digital Satellite Receiver
Model:	DBS6600 MINI
Brand:	LEXIUM
Applicant:	**WS International** 1200 Cobb Parkway North Suite 100B Marietta, Georgia 30062 USA
Manufacturer:	**WS International** 1200 Cobb Parkway North Suite 100B Marietta, Georgia 30062 USA
Tested:	October 25, 2011 – October 26, 2011
Test Voltage:	120VAC, 60Hz

EMISSION			
Standard	**Item**	**Result**	**Remarks**
FCC 47 CFR Part 15 Subpart B (October 1, 2010), ICES-003 Issue 4 ANSI C63.4-2009	Conducted (Power Port)	PASS	Meet Class B limit
	Radiated (Below 1GHz)	PASS	Meet Class B limit
	Radiated (Above 1GHz)	N/A	No Requirement
FCC 47 CFR Part 15 Subpart B Section 15.111	Antenna Power	PASS	Meet the limit

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
2. The information of measurement uncertainty is available upon the customer's request.

Deviation from Applicable Standard
None

The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by: ***Reviewed by:***

Jeter Wu
Assistant Manager

Eric Huang
Assistant Section Manager

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

2 EUT DESCRIPTION

Product	Digital Satellite Receiver
Model	DBS6600 Mini
Data Applies To	DBS8000
Brand Name	LEXIUM
Applicant	WS International
Housing material	Plastics
Identify Number	T111025404
Received Date	October 25, 2011
EUT Power Rating	120-240Vac, 14W, 50-60Hz

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
1. N/A	---	---

Note:

1. Client consigns two model samples to test (Model Number: DBS6600 Mini). Therefore, the testing Lab. just guarantees the unit, which has been tested.
2. For more details, please refer to the User's manual of the EUT.
3. According to customer declaration, the EUT included remote controller for sale.
4. To add a series model is for business necessary, just for marketing purpose only.

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3 TEST METHODOLOGY

3.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the above additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The test configuration/ modes are as the following:

Conduction Modes:

1.	**Normal Operation**

Radiation Modes: (Below 1GHz)

1.	**Normal Operation**

Radiation Modes: (Above 1GHz)

1.	**N/A**

Antenna Modes:

1.	**Normal Operation**

3.2. EUT SYSTEM OPERATION

1). Setup whole system for test as shown on setup diagram.
2). Turn on power and check function.
3). Start to test by test mode.

Note: Test program is self-repeating throughout the test.

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3.3. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Peripherals Devices:

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	LCD TV	OLEVIA	D20533	DOC	Power Cable, unshd, 1,8m

No.	Signal cable description	
A	Power Line	Unshielded, 1.6m 1 pcs
B	AV	Shielded, 1.2m 1 pcs
C	Coaxial Cable	Shielded, 1.4m 1 pcs
D	Coaxial	Shielded, 1.5m 2 pcs

Note:
1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3.4. CONFIGURATION OF SYSTEM UNDER TEST



Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4 FACILITIES AND ACCREDITATIONS

4.1. FACILITIES

All measurement facilities used to collect the measurement data are located at:

☒ No.8,Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4, CISPR 16-1-5.

4.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

Taiwan	TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Germany	TUV NORD
Taiwan	BSMI
USA	FCC

Copies of granted accreditation certificates are available for downloading from our web site, http:///www.ccsrf.com

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement		Frequency	Uncertainty
Power Line Conducted Emission		9kHz~30MHz	±2.90dB
Radiated Emission (10m)	Test Site : OATS-5	30 MHz ~200 MHz	±3.76dB
		200 MHz ~1000 MHz	±3.73dB
	Test Site : OATS-6	30 MHz ~200 MHz	±3.60dB
		200 MHz ~1000 MHz	±3.70dB
	Test Site : OATS-7	30 MHz ~200 MHz	±3.99dB
		200 MHz ~1000 MHz	±3.31dB
Radiated Emission (3m)	Test Site : OATS-5	30 MHz ~200 MHz	±3.38dB
		200 MHz ~1000 MHz	±3.27dB
	Test Site : OATS-6	30 MHz ~200 MHz	±3.59dB
		200 MHz ~1000 MHz	±3.27dB
	Test Site : OATS-6	1000 MHz ~6000 MHz	±3.20dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22: 2006, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than UCISPR which is 3.6dB and 5.2dB respectively. CCS values (called ULab in CISPR 16-4-2) is less than UCISPR as shown in the table above. Therefore, MU need not be considered for compliance.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5 CONDUCTED EMISSION MEASUREMENT

5.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE:

(1) The lower limit shall apply at the transition frequencies.
(2) The limit decreases in line with the logarithm of the frequency in the range 0.15 to 0.50 MHz.
(3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

5.2. TEST INSTRUMENTS

Conducted Emission room # 1				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
L.I.S.N.	SCHWARZBECK	NNLK 8121	8121-308	MAR. 09, 2012
TEST RECEIVER	Rohde & Schwarz	ESCS 30	100348	JUL. 13, 2012
BNC COAXIAL CABLE	CCS	BNC50	11	OCT. 04, 2012
Test S/W	e-3 (5.04211c) R&S (2.27)			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.3. TEST PROCEDURES

Procedure of Preliminary Test

- The EUT and support equipment, if needed, were set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- The test equipment EUT installed by AC 120VAC/60Hz main power, through a Line Impedance Stabilization Network (LISN), which was supplied power source and was grounded to the ground plane.
- All support equipment power by from a second LISN.
- The test program of the EUT was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- The test data of the worst-case condition(s) was recorded.

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.5. DATA SAMPLE:

Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Meter Reading (dBuV)	Measured Level (dBuV)	Limits (dBuV)	Over Limits (dBuV)	Detector
x.xx	9.6	0.1	15.7	25.4	46	-20.6	QP

Freq. = Emission frequency in MHz
LISN Factor = Insertion loss of LISN and Pulse Limiter
Cable Loss = Cable's loss (LISN to EMI Tester Receiver)
Meter Reading = Uncorrected Analyzer/Receiver reading
Measured Level = Meter Reading + LISN Factor + Cable loss
Limit = Limit stated in standard
Over Limit = Measured Level - Limits
Detector : Peak/PK = Peak Reading
QP = Quasi-peak Reading
AV = Average Reading

Calculation Formula

1. Measured Level (dBuV) = LISN Factor (dB) + Cable Loss (dB)+ Meter Reading (dBuV)
2. Over Limit (dBuV) = Measured Level (dBuV) – Limits (dBuV)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.6. TEST RESULTS

Model No.	DBS6600 Mini	6dB Bandwidth	9 kHz
Environmental Conditions	25deg.C, 58% RH	Test Mode	Normal Operation
Tested by	Ted Huang		

Line

(The chart below shows the highest readings taken from the final data.)



Freq. MHz	LISN Factor dB	Cable Loss dB	Meter Reading dBuV	Measured Level dBuV	Limits dBuV	Over Limits dBuV	Detector
0.17	8.64	0.01	39.50	48.15	64.86	-16.70	QP
0.17	8.64	0.01	28.17	36.82	54.86	-18.03	AVERAGE
0.23	8.65	0.01	24.38	33.04	52.30	-19.26	AVERAGE
0.23	8.65	0.01	35.10	43.76	62.30	-18.54	QP
0.57	8.64	0.02	25.22	33.88	46.00	-12.12	AVERAGE
0.57	8.64	0.02	35.24	43.90	56.00	-12.10	QP
0.75	8.61	0.02	20.67	29.30	46.00	-16.70	AVERAGE
0.75	8.61	0.02	32.88	41.51	56.00	-14.49	QP
1.40	8.62	0.02	20.14	28.78	46.00	-17.22	AVERAGE
1.40	8.62	0.02	30.00	38.64	56.00	-17.36	QP
2.30	8.64	0.02	28.90	37.56	56.00	-18.44	QP
2.30	8.64	0.02	19.01	27.67	46.00	-18.33	AVERAGE
16.66	8.78	0.15	26.70	35.63	60.00	-24.37	QP
16.66	8.78	0.15	19.70	28.63	50.00	-21.37	AVERAGE

NOTE:

1. Measured Level (dBuV) = LISN Factor (dB) + Cable Loss (dB)+ Meter Reading (dBuV)
2. Over Limit (dBuV) = Measured Level (dBuV) – Limits (dBuV)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Model No.	DBS6600 Mini	6dB Bandwidth	9 kHz
Environmental Conditions	25deg.C, 58% RH	Test Mode	Normal Operation
Tested by	Ted Huang		

Neutral
(The chart below shows the highest readings taken from the final data.)



Freq. MHz	LISN Factor dB	Cable Loss dB	Meter Reading dBuV	Measured Level dBuV	Limits dBuV	Over Limits dBuV	Detector
0.17	8.64	0.01	36.84	45.49	65.12	-19.63	QP
0.17	8.64	0.01	21.03	29.68	55.12	-25.44	AVERAGE
0.22	8.65	0.01	32.22	40.88	62.70	-21.82	QP
0.22	8.65	0.01	15.04	23.70	52.70	-29.00	AVERAGE
0.48	8.65	0.02	28.48	37.15	56.41	-19.26	QP
0.48	8.65	0.02	11.84	20.51	46.41	-25.90	AVERAGE
0.57	8.64	0.02	29.74	38.40	56.00	-17.60	QP
0.57	8.64	0.02	14.04	22.70	46.00	-23.30	AVERAGE
0.72	8.61	0.02	25.32	33.95	56.00	-22.05	QP
0.72	8.61	0.02	8.30	16.93	46.00	-29.07	AVERAGE
1.44	8.63	0.02	11.75	20.40	46.00	-25.60	AVERAGE
1.44	8.63	0.02	25.46	34.11	56.00	-21.89	QP
16.66	8.78	0.15	26.34	35.27	60.00	-24.73	QP
16.66	8.78	0.15	18.35	27.28	50.00	-22.72	AVERAGE

NOTE:

1. Measured Level (dBuV) = LISN Factor (dB) + Cable Loss (dB)+ Meter Reading (dBuV)
2. Over Limit (dBuV) = Measured Level (dBuV) – Limits (dBuV)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6 RADIATED EMISSION MEASUREMENT

6.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Below 1GHz (for digital device)

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHZ)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. The measurement above 1GHz is at close-in distances 3m,and determine the limit L_2 corresponding to the close-in distance d_2 by applying the following relation: $L_2 = L_1 (d_1/d_2)$, where L_1 is the specified limit in microvolts per metre (**uV/m**) at the distance d_1 (**10m**), L_2 is the new limit for distance d_2 (**3m**).
So the new Class A limit above 1GHz at 3m is as following table:

Frequency (MHZ)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.75	30
1.75-108	1000
108-500	2000
500-1000	5000
Above 1000	5^{th} harmonic of the highest frequency or 40GHz, whichever is lower

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6.2. TEST INSTRUMENTS

Open Area Test Site # 5				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
TEST RECEIVER	Rohde & Schwarz	ESCS 30	100294	MAR. 09, 2012
TYPE N COAXIAL CABLE	SUHNER	RG_214_U/2X	5	NOV. 24, 2011
BILOG ANTENNA	Sunol sciences	JB1	A070506-1	OCT. 07, 2012
Test Software	EMI e-3 / AUDIX (5.04211c)			
Above 1GHz Used				
RF Cable	SUHNER	SUCOFLEX104PEA	20520/4PEA	NOV. 10, 2012
Horn Antenna	Com-Power	AH-118	071032	DEC. 27, 2011
Spectrum Analyzer	R&S	FSEK 30	835253/002	JUL. 14, 2012
Pre-Amplifier	MITEQ	AFS44-00108650-42-10P-44	1205908	NOV. 23, 2011
Turn Table	Yo Chen	001	----------	N.C.R.
Antenna Tower	AR	TP1000A	309874	N.C.R.
Controller	CT	SC101	----------	N.C.R.
RF Swicth	E-INSTRUMENT TELH LTD	ERS-180A	EC1204141	N.C.R
Test Software	e-3 (5.04303e)			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. N.C.R = No Calibration Request.

Draft

6.3. TEST PROCEDURES

Procedure of Preliminary Test

- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC 120VAC/60Hz power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Procedure of Final Test

- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 or 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.
- The test data of the worst-case condition(s) was recorded.

6.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6.5. DATA SAMPLE

Below 1GHz

Freq. (MHz)	Reading dBuV/m	Antenna Factor dB	Cable loss dB	Measure level dBuV/m	Limit dBu/m	Over limit dBuV/m	Detector
x.xx	24.48	7.33	1.50	33.31	40	-6.69	QP

Freq. = Emission frequency in MHz
Reading = Uncorrected Analyzer/Receiver reading
Antenna Factor = Antenna Factor - Amplifier Gain
Cable los = Cable's loss
Measure level = Reading + Antenna Factor + Cable loss
Limit = Limit stated in standard
Over limit = Measure level – Limit
Detector: Peak/PK = Peak Reading
QP = Quasi-peak Reading
AV = Average Reading

Calculation Formula

Over limit (dBuV/m) = Result (dBuV/m) – Limit (dBuV/m)

Above 1GHz

Freq.	Reading	AF	Closs	Pre-amp	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBμV)	(dBμV)	(dB)	(dB)	dB	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	(Meter)
XXXX. XX	56.00	25.14	2.07	41.77	0.72	42.16	70.00	-27.84	P	1.00

Freq. = Emission frequency in MHz
Reading = Uncorrected Analyzer/Receiver reading
AF = Antenna Factor
Closs = Cable's loss
Pre-amp = Pre-amp Gain
Filter = Insertion loss of filter
Level = Readind+AF+Closs-Pre-amp+Fliter
Limit = Limit stated in standard
Margin = Reading in reference to limit
Mark: P = Peak Reading
Q= Quasi-peak Reading
A = Average Reading
Height = Antenna Height

Calculation Formula

Margin (dB) =Level (dBuV/m) – Limit (dBuV/m)

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6.6. TEST RESULTS

Below 1GHz

Model No.	DBS6600 Mini	**Test Mode**	Normal Operation
Environmental Conditions	25.5deg.C, 47% RH	**6dB Bandwidth**	120 kHz
Antenna Pole	Vertical	**Antenna Distance**	10m
Detector Function	Quasi-peak.	**Tested by**	Vision Chang

(The chart below shows the highest readings taken from the final data.)



Trace: (Discrete)

Freq. MHz	Reading Level dBuV	Antenna Factor dB/m	Cable Loss dB	Measure Level dBuV/m	Limit dBuV/m	Over Limit dBuV/m	Detector
33.18	7.51	19.29	1.20	28.00	40.00	-12.00	QP
180.00	17.02	11.60	3.40	32.02	43.50	-11.48	QP
202.83	14.21	13.32	3.62	31.16	43.50	-12.34	QP
360.00	7.55	15.56	5.16	28.27	46.00	-17.73	QP
718.96	7.31	20.94	7.79	36.05	46.00	-9.95	QP
960.00	3.21	23.27	9.08	35.56	46.00	-10.44	QP

Note:

1. QP= Quasi-peak Reading.
2. The other emission levels were very low against the limit.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Model No.	DBS6600 Mini	**Test Mode**	Mode 1
Environmental Conditions	25.5deg.C, 47% RH	**6dB Bandwidth**	120 kHz
Antenna Pole	Horizontal	**Antenna Distance**	10m
Detector Function	Quasi-peak.	**Tested by**	Vision Chang

(The chart below shows the highest readings taken from the final data.)



Trace: (Discrete)

Freq. MHz	Reading Level dBuV	Antenna Factor dB/m	Cable Loss dB	Measure Level dBuV/m	Limit dBuV/m	Over Limit dBuV/m	Detector
180.00	18.07	11.60	3.40	33.07	43.50	-10.43	QP
200.23	15.02	13.45	3.60	32.07	43.50	-11.43	QP
274.85	8.75	13.24	4.25	26.24	46.00	-19.76	QP
480.06	4.85	17.76	5.84	28.45	46.00	-17.55	QP
633.83	4.51	19.88	7.16	31.56	46.00	-14.44	QP
960.00	2.75	23.27	9.08	35.11	46.00	-10.89	QP

Note:

1. QP= Quasi-peak Reading.
2. The other emission levels were very low against the limit.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Above 1GHz

※ No applicable, since the highest frequency of the internal sources of the EUT is less than 108MHz, the measurement shall only be made up to 1 GHz.

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7 ANTENNA POWER MEASUREMENT (SECTION 15.111)

7.1. LIMITS OF ANTENNA POWER CONDUCTED MEASUREMENT

FREQUENCY (MHz)	Maximum Field Strength Limit (dBuV)
30 ~ 960	51

7.2. TEST INSTRUMENTS

Antenna Power Conducted Test Site				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
TEST RECEIVER	Rohde & Schwarz	ESCS 30	100348	JUL. 03, 2012
BNC COAXIAL CABLE	CCS	BNC50	11	OCT. 04, 2012
Test S/W	e-3 (5.04211c) R&S (2.27)			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3. TEST PROCEDURES

- The test item can be in deliver on shielding room.
- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- The EUT received AC power source, 120VAC/60Hz, from the outlet socket under the turntable. All support equipment received power from another socket under the turntable.
- With the 75←→50Ω matching network when the connected coaxial cable of impedance not matching.
- The output level of the auxiliary signal generator shall be set to give the value of 60 dB (μV) for FM receiver or 70 dB (μV) for TV and VCR to the input of the frequency-modulation or television receiver (or video recorder) respectively, on a 75Ω impedance. An additional amplifier should be insert at the generator output, if necessary.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- The results shall be expressed in the terms of the substitution power in nanowatt (nW), as supplied by the standard signal generator. The specified source impedance of the receiver shall be stated with the results.
- When measurements are made at the antenna terminals of the equipment under test, an auxiliary signal generator shall be used to feed the equipment under test input with a standard test signal at the receiver tuning frequency (30MHz to 5000MHz).
- The test mode(s) described in Item 3.2 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.2 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Procedure of Final Test

- EUT and support equipment were set up on the turntable as per step 8 of the preliminary test.
- The receiver scanned from 30MHz to 5000MHz, recorded the value, the local frequency, amplitude, were recorded in which correction factors were used to calculate the emission level and compare reading to the applicable limit. The power at the antenna terminal at any frequency within the range of measurement shall not exceed 2.0 The receiver scanned from 30MHz to 5000MHz, recorded the value, the local frequency, amplitude, were recorded in which correction factors were used to calculate the emission level and compare reading to the applicable limit. The power at the antenna terminal at any frequency within the range of measurement shall not exceed 2.0 nanowatt.
- The test data of the worst case condition(s) was recorded.

7.4. DATA SAMPLE:

Freq. (MHz)	Reading 【dBuV】	Limit 【dBuV】	Margin 【dBuV】
xx.xx	0.30	51.00	-1.70

Freq. = Emission frequency in MHz
Reading (nW) = Uncorrected Analyzer / Receiver reading
Limit (nW) = Limit stated in standard
Margin (nW) = Reading in reference to limit

Draft

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.5. TEST RESULTS

Model No.	DBS6600 MINI	**Test Mode**	Normal Operation
Environmental Conditions	25°C, 58% RH	**6dB Bandwidth**	120 kHz
Detector Function:	Quasi-peak.	**Tested by:**	Ted Huang



Trace: (Discrete)

Freq. MHz	LISN Factor dB	Cable Loss dB	Meter Reading dBuV	Measured Level dBuV	Limits dBuV	Over Limits dBuV	Detector
37.29	0.00	3.30	12.28	15.58	51.00	-35.42	QP
62.00	0.00	3.54	12.76	16.30	51.00	-34.70	QP
112.92	0.00	3.81	12.50	16.31	51.00	-34.69	QP
194.45	0.00	4.06	12.52	16.58	51.00	-34.42	QP
416.18	0.00	4.42	12.80	17.22	51.00	-33.78	QP
742.26	0.00	5.13	12.80	17.93	51.00	-33.07	QP

Note:

1. QP= Quasi-peak Reading.
2. The other emission levels were very low against the limit.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

RADIATED EMISSION TEST





This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

ANTENNA POWER CONDUCTED EMISSION TEST (SECTION 15.111)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.